




# XTM 201DI Digital Multi-Process Inverter

**NEW**



**NEW dual voltage multi-process mig welder with digital interface, ideal for maintenance and multi process applications.**

STOCK CODE	DESCRIPTION
XTM201DI	200A MIG MULTI INC, MMA Lead Set and Gas hose.
XTM201DI-P1	200A MIG MULTI INC, MMA Lead Set, Remote Control MIG Torch, Gas hose, regulator
XTM201DI-P2	200A MIG MULTI INC, MMA Lead Set, Remote Control MIG Torch, PRO 17 TIG Torch, Gas hose, regulator
XTM201DI-PE	200A MIG MULTI INC Remote Control MIG Torch, 5KG Wire and MMA Lead Set.
XTM201DI-T	200A MIG MULTI INC, MMA Lead Set, Trolley.
XTM201DI-P1T	200A MIG MULTI INC, MMA Lead Set, Remote Control MIG Torch, Gas hose, regulator, Trolley
XTM201DI-P2T	200A MIG MULTI INC, MMA Lead Set, Remote Control MIG Torch, PRO 17 TIG Torch, Gas hose, regulator, Trolley
XTM201DI-PTE	200A MIG MULTI INC Remote control MIG torch, 5KG wire and MMA lead set and Trolley.
XTM201DI-AL	Aluminium MIG Welding Starter Kit Inc 0.8-1.0 U Roller and Teflon Liner 3m, 1.0mm Contact Tip.
PRO17-12S1MPGD	PRO17 TIG Torch 12ft Single Trigger with 1.6mm Tungsten and 11mm Nozzle.
PRO2500-30ER4	250A Remote Control MIG Torch 3m with 4 Button Control.

## Technical Information

PARAMETER	VALUE
Style	Portable
Machine type	Inverter MIG/TIG/MMA
Wire feed speed	3.5-10m/min
Voltage range	MIG 14.5-24V, TIG 10.4-18V, MMA 20.4-28V
Spool size	100mm and 200mm (1-5kg)
Feed box	2 Roll
Wire size	0.6, 0.8, 0.9, 1.0 (0.8/1.0 inc)
Duty cycle	200A @ 25% (230V)
Input voltage	110V/230V
Maximum current	140A\200A
Minimum current	30A (MIG), 10A (TIG)
Input current(Max)	32A/26A
Fuse rating	32A/16A
KVA	3.7
Enclosure protection	IP23S
Dimensions (mm)	490 x 220 x 430
Weight	17.5kg
Languages	English, Espanol, Deutsche, Francais, Svenska, Polskaie

Go to page 50 for more information on the control handle